

MEDIUM PRESSURE PERFORMANCE

Model	Standard Air Delivery (CFM)											RPM	Motor HP	Approx. Weight (lbs.)
	Free Air	Static Pressure (Inches of Water)												
		1/4"	1/2"	3/4"	1"	1 1/4"	1 1/2"	1 3/4"	2"	2 1/4"	2 1/2"			
RTAF-12	1900	1800	1650	1450	1150	500						3450	1/3	85
	2150	2100	2050	2000	1900	1800	1750	1650	1500			3450	1	95
RTAF-16	3350	3200	3050	2850	2650	2400	2050	1550	1350			3450	1	105
	5400	5350	5100	4900	4700	4500	4250	3650	3500			3450	2	120
	6300	6150	5950	5750	5550	5300	5000	4750	4300			3450	3	135
RTAF-20	6500	6250	6000	5750	5500	5200	4900	4550	4150	3600	2900	3450	2	125
	8300	8000	7700	7500	7200	6950	6700	6450	6100	5600	5000	3450	3	160
	10300	10100	9800	9500	9300	9000	8700	8400	8100	7600	7100	3450	5	165
RTAF-24	9000	8100	7200	3900	2200							1725	1	230
	10000	9600	9200	8700	8200	7700	7200	6600	6000	5400	4500	3450	3	250
	13000	12600	12100	11600	11100	10500	9900	9300	8600	7900	6900	3450	5	255
	15300	14900	14500	14100	13700	13300	12900	12400	11900	11300	10700	3450	7.5	265
RTAF-30	12000	11500	11000	10400	9600	8600	7500	5400	4600			1725	3	350
	15400	14900	14300	13700	13000	12200	11200	9600	6000			1725	5	360
	19600	19000	18400	17800	17000	16200	15400	14000				1725	7.5	270

*Minimum 1/4 HP motors are usually furnished where ratings for 1/8 HP and less are specified; the next higher HP rating is usually furnished in place of 1/3, 3/4, and some 1 1/2 HP ratings.